



Digits	4
Digit height	20mm
Color	Red
Reading	9999/-1999
Frontal	96x48mm
Mounting	Panel
Power	H (85-265Vac/dc) L (11-60Vdc and 24/48Vac)
Output and control options	Relay outputs (1 to 6) Analog outputs MODBUS RTU RS-485 RS-232
Accessories	Wall mount DIN rail mount Benchtop housing Adapter 96x96mm Labeling units
Main features	Reading up to 8 meters Front keypad configuration Up to 3 output and control options Isolated circuits Protection IP54/IP65 Configurable brightness levels Advanced alarm management Function 'Fast Access' Function 'On power up' Max. and min. memory Function password Optional without front keypad Modular internal architecture Plug-in screw terminals High quality front lens
Main function / Input signal	For Process For Pt100/RTD and Thermocouples Counter, Ratemeter, Periodmeter AC Voltmeter and AC Ammeter DC Voltmeter and DC Ammeter AC Frequencymeter for AC power lines Chronometer, Time counter For Potentiometers For Modbus RTU protocol For RS-485 ASCII protocol For RS-232 ASCII protocol

The Series K of digital panel meters offers versatility and reliability in all type of industrial applications. The 20mm digit height provide an excellent reading for a distance of up to 8 meters. The joint use of 7 segment red leds with a specially adapted front lens, provides a sharp and clean reading.






The visual lines of the Series K stand for a clean and wide front space, where the main role is focused on the value displayed. The configuration keypad together with the units label and the logo, are located at the bottom, and do not visually interfere with the value displayed.

The Series K stands out for its security : all circuits are isolated between them, and excitation voltages are protected against short circuits. Internal components (such as leds, microcontrollers, push buttons, terminals, ...) are acquired to high reputation brands, it mounts plug-in screw terminals for safe connections, a housing specifically designed at FEMA, a patented panel fixation and front labeling units with high quality industrial adhesive.







The Series K internal architecture features a modular design providing flexibility to replace, add or change any of its internal modules to expand functionality as needed.

In short, the Series K offers a wide range of digital panel meters, with multiple functions, allowing for a high level of customization, and a wide variety of references for analog and digital signals. A series adapted to the needs of the industry, with the differential of its 20mm digits height.

# MODELS






Model	K40-P	K40-T	K40-A	K40-D	K40-F
<b>Main function</b>	PROCESS METER 	TEMPERATURE METER 	AC VOLTMETER AC AMMETER 	DC VOLTMETER DC AMMETER 	AC FREQUENCYMETER FOR POWER LINES 
<b>Ranges</b>	0/10Vdc, 4/20mA, ±10Vdc,±20mA	Pt100/RTD (2 and 3 wires) Thermocouples J, K, T, E, S, R, N, C, L y X	600Vac, 100Vac, 10Vac, 1Vac, 100mVac, 5Aac, 1Aac	±600Vdc, ±100Vdc, ± 10Vdc, ±1Vdc, ±100mVdc, ±5Adc, ±1Adc	Frequencymeter up to 900KHz @500Vac
<b>Digits</b>	4	4	4	4	4
<b>Reading</b>	9999/-1999	9999/-1999	9999/-1999	9999/-1999	9999/-1999
<b>Digit height</b>	20mm	20mm	20mm	20mm	20mm
<b>Channels</b>	1	1	1	1	1
<b>Excitation voltage</b>	5 to 20Vdc (max. 35mA)	---	---	---	---
<b>Notes</b>	---	---	TrueRMS measure CAT-II and CAT-III AC or AC+DC coupling	---	---
<b>Total error</b>	<0,05%	<0,2°C Pt100/RTD <2°C/<4°C thermocouples	<0,15% a <0,25%	<0,10% a <0,15%	<0,05%
<b>Thermal drift</b>	10ppm/°C (offset) 25ppm/°C (offset+span)	0,05°C/°C a 0,02°C/°C (offset) 0,02°C/°C a 0,2°C/°C (offset+span)	<75 a <150ppm/°C (offset) <100 a <200ppm/°C (offset+span)	50ppm/°C (offset) 100ppm/°C (offset+span)	20ppm/°C
<b>Step response</b>	<120mSec.	---	<300mSec.	<210mSec.	---
<b>Acquisitions</b>	15/second	3/second	15/second	15/second	---
<b>Power</b>	H (85-265Vac/dc) L (11-60Vdc and 24/48Vac)	H (85-265Vac/dc) L (11-60Vdc and 24/48Vac)	H (85-265Vac/dc) L (11-60Vdc and 24/48Vac)	H (85-265Vac/dc) L (11-60Vdc and 24/48Vac)	H (85-265Vac/dc) L (11-60Vdc and 24/48Vac)
<b>Consumption</b>	<1,5W (meter only) <4,0W (with options)	<1,5W (meter only) <4,0W (with options)	<1,5W (meter only) <4,0W (with options)	<1,5W (meter only) <4,0W (with options)	<1,5W (meter only) <4,0W (with options)
<b>Isolation</b>	2500Veff (H) 1500Veff (L)	2500Veff (H) 1500Veff (L)	2500Veff (H) 1500Veff (L)	2500Veff (H) 1500Veff (L)	2500Veff (H) 1500Veff (L)
<b>Protection</b>	IP54/IP65	IP54/IP65	IP54/IP65	IP54/IP65	IP54/IP65
<b>Output and control options</b>	Maximum 3	Maximum 3	Maximum 3	Maximum 3	Maximum 3
<b>Particular functions of this model</b>	Scalable reading 20 segment linearization Display filters Function 'Measure' Function 'Field correction' Function 'Tare' Alarms 'Peak&Hold'	Automatic and configurable cold junction compensation Reading in °C or °F Manual offset for Pt100/RTD Pt100/RTD resolution selectable 1°C or 0,1°C	Scalable reading Display filters Function 'Measure' Function 'Field correction' Alarms	Scalable reading Display filters Function 'Measure' Function 'Field correction' Alarms	Scalable reading Alarms
<b>Common functions</b>	Function 'Fast access' Function 'On power up' 5 brightness levels Max. and min. memory Password	Function 'Fast access' Function 'On power up' 5 brightness levels Max. and min. memory Password	Function 'Fast access' Function 'On power up' 5 brightness levels Max. and min. memory Password	Function 'Fast access' Function 'On power up' 5 brightness levels Max. and min. memory Password	Function 'Fast access' Function 'On power up' 5 brightness levels Max. and min. memory Password
<b>Labeling units</b>	Includes units label Units1	Includes units label Units3	Includes units label Units2	Includes units label Units2	Includes units label Units4
<b>Configuration</b>	From front keypad	From front keypad	From front keypad	From front keypad	From front keypad
<b>Mounting</b>	Panel (optional wall mount and DIN rail)	Panel (optional wall mount and DIN rail)	Panel (optional wall mount and DIN rail)	Panel (optional wall mount and DIN rail)	Panel (optional wall mount and DIN rail)
<b>Weight</b>	<150gr	<150gr	<150gr	<150gr	<150gr
<b>Depth</b>	91mm	91mm	91mm	91mm	91mm

# MODELS AND REFERENCES SERIES K




K40-C1	K40-CR	K40-R	K40-RTU	K40-485	K40-232
COUNTER, RATEMETER, PERIODMETER 	CHRONOMETER TIME COUNTER 	POTENTIOMETRIC METER 	MODBUS RTU REPEATER 	RS-485 ASCII REPEATER 	RS-232 ASCII REPEATER 
Impulse counter up to 250KHz Ratemeter up to 900KHz Periodmeter up to 1000sec.	Hours, minutes, seconds, tenths and cents of second Hour or decimal format	Pot<5K, Pot<5M, passive mode	Protocol Modbus RTU	Protocol RS-485 ASCII	Protocol RS-232 ASCII
4	4	4	4	4	4
9999/-1999	9999/-1999	9999/-1999	9999/-1999	9999/-1999	9999/-1999
20mm	20mm	20mm	20mm	20mm	20mm
1	1	1	1	1	1
5 to 18Vdc (max. 70mA)	5 to 18Vdc (max. 70mA)	+5Vdc	---	---	---
Highly configurable Accepts all type of sensors (NPN, PNP, ...) Accepts quadrature signals Front and/or rear reset	Independent start, stop and reset controls Up and down counting Highly configurable Front and/or rear reset Memory in case of power loss Accepts all type of controls (NPN, PNP, ...)	---	---	---	---
---	<0,01%	<0,15%	---	---	---
---	20ppm/°C	10ppm/°C (offset) 35ppm/°C (offset+span)	---	---	---
---	---	<200mSec.	---	---	---
---	---	5/second	---	---	---
H (85-265Vac/dc) L (11-60Vdc and 24/48Vac)	H (85-265Vac/dc) L (11-60Vdc and 24/48Vac)	H (85-265Vac/dc) L (11-60Vdc and 24/48Vac)	H (85-265Vac/dc) L (11-60Vdc and 24/48Vac)	H (85-265Vac/dc) L (11-60Vdc and 24/48Vac)	H (85-265Vac/dc) L (11-60Vdc and 24/48Vac)
<1,5W (meter only) <4,0W (with options)	<1,5W (meter only) <4,0W (with options)	<1,5W (meter only) <4,0W (with options)	<1,5W (meter only) <4,0W (with options)	<1,5W (meter only) <4,0W (with options)	<1,5W (meter only) <4,0W (with options)
2500Veff (H) 1500Veff (L)	2500Veff (H) 1500Veff (L)	2500Veff (H) 1500Veff (L)	2500Veff (H) 1500Veff (L)	2500Veff (H) 1500Veff (L)	2500Veff (H) 1500Veff (L)
IP54/IP65	IP54/IP65	IP54/IP65	IP54/IP65	IP54/IP65	IP54 / IP65
Maximum 3	Maximum 3	Maximum 3	Maximum 3	Maximum 3	Maximum 3
8 selectable working modes (inhibit, subtract, quadrature, ...) Scalable reading (multiplier and divider) Configurable preset Special 'Fast' counter mode Special 'Slow' ratemeter mode Function 'Trigger Sense' Function 'On alarm'	12 reading formats (hour / decimal). Time cycles, accumulated time, hold, ... Up and down counting Preset Special control functions Configurable trigger level Repeatable cycles of counting	Scalable reading 20 segment linearization Display filters Function 'Measure' Function 'Field correction' Function 'Tare' Alarms	'Slave' or 'Process' modes Function 'Watchdog' Configurable 16 bits or 32 bits registers Function 'Bus Activity'	'Slave', 'Process' or 'Text' modes Function 'Watchdog' Function 'Bus Activity'	'Slave', 'Process' or 'Text' modes Function 'Watchdog' Function 'Bus Activity'
Function 'Fast access' Function 'On power up' 5 brightness levels Max. and min. memory Password	Function 'Fast access' Function 'On power up' 5 brightness levels Max. and min. memory Password	Function 'Fast access' Function 'On power up' 5 brightness levels Max. and min. memory Password	Function 'Fast access' Function 'On power up' 5 brightness levels Max. and min. memory Password	Function 'Fast access' Function 'On power up' 5 brightness levels Max. and min. memory Password	Function 'Fast access' Function 'On power up' 5 brightness levels Max. and min. memory Password
Includes units label Units5	Includes units label Units6	Includes units label Units1	Includes units label Units1	Includes units label Units1	Includes units label Units1
From front keypad	From front keypad	From front keypad	From front keypad	From front keypad	From front keypad
Panel (optional wall mount and DIN rail)	Panel (optional wall mount and DIN rail)	Panel (optional wall mount and DIN rail)	Panel (optional wall mount and DIN rail)	Panel (optional wall mount and DIN rail)	Panel (optional wall mount and DIN rail)
<150gr	<150gr	<150gr	<150gr	<150gr	<150gr
91mm	91mm	91mm	91mm	91mm	91mm





# OUTPUT AND CONTROL OPTIONS



Option	R1	A0	RTU	S4	S2
<b>Main function</b>	1 RELAY OUTPUT 	1 ANALOG OUTPUT 	1 MODBUS RTU 	1 RS-485 ASCII 	1 RS-232 ASCII 
<b>Characteristics</b>	3 terminals (NC, NO, common) 250Vac, max. 8A	Output in 4/20mA, 0/10Vdc	Up to 38.400bps	Up to 38.400bps	Up to 38.400bps
<b>Isolation</b>	Yes, 3500Veff	Yes, 1000Vdc	Yes, 1000Vdc	Yes, 1000Vdc	Yes, 1000Vdc
<b>Maximum number of options installable</b>	1, 2 or 3	1, 2 or 3	1, 2 or 3	1, 2 or 3	1, 2 or 3
<b>Installable at</b>	Option 1, 2 and 3	Option 1, 2 and 3	Option 1, 2 and 3	Option 1, 2 and 3	Option 1, 2 and 3
<b>Notes</b>	For 2 (or 3) relay outputs, reference R1-R1 (or R1-R1-R1).	Output signal configurable for active and passive. Direct and inverse slope.			







## SPECIAL OPTIONS

Option	R2	R4	R6
<b>Main function</b>	2 RELAY OUTPUTS 	4 RELAY OUTPUTS 	6 RELAY OUTPUTS 
<b>Characteristics</b>	3 terminals (NC, NO, common) 250Vac, Maximum 6 A	3 terminals (NC, NO, common) 250Vac, Maximum 6 A	3 terminals (NC, NO, common) 250Vac, Maximum 6 A
<b>Isolation</b>	Yes, 2500Veff	Yes, 2500Veff	Yes, 2500Veff
<b>Maximum number of options installable</b>	1	1	1
<b>Installable at</b>	Option 1	Option 1	Option 1
<b>Notes</b>	This special option is not compatible with other options R1, R2, R4 or R6. Installs at Option 1 and leaves free options 2 and 3.	This special option is not compatible with other options R1, R2, R4 or R6. Installs at Option 1 and 2 and leaves free Option 3.	This special option is not compatible with other options R1, R2, R4 or R6. Installs at Option 1, 2 and 3.

## OTHER OPTIONS

Option	65	NBT
<b>Main function</b>	FRONT IP65 	WITHOUT FRONT KEYPAD 
<b>Characteristics</b>		
<b>Isolation</b>		
<b>Maximum number of options installable</b>		
<b>Installable at</b>		
<b>Notes</b>	The Front IP65 blocks access to internal modules. Internal modules can not be added or replaced without breaking the Front IP65 protection seal.	The front keypad is not accessible to the operator. To access the keypad, uninstall the instrument from the panel, and remove the front filter.

Option	DRA-M	KA96	THM	KIP	WME
<b>Main function</b>	DIN RAIL ADAPTER 	ADAPTER 96X96mm 	BENCHTOP HOUSING 	IP65 FRONT COVER 	WALL MOUNT HOUSING 
<b>Notes</b>	Adapter for DIN rail mounting. For panel meters with front size 96x48mm.	Adapter for 96x96mm front size. For panel meters with front size 96x48mm.	Benchtop housing. For panel meters with front size 96x48mm.	Removable front cover that provides IP65 protection. For panel meters with front size 96x48mm. Allows access to the front of the instrument.	Wall mount housing. For panel meters with front size 96x48mm. Together with KIP front cover, it provides full IP65 protection.

Option	LABEL UNITS1	LABEL UNITS2	LABEL UNITS3	LABEL UNITS4	LABEL UNITS5	LABEL UNITS6
<b>Main function</b>	LABEL WITH PRINTED UNITS 	LABEL WITH PRINTED UNITS 	LABEL WITH PRINTED UNITS 	LABEL WITH PRINTED UNITS 	LABEL WITH PRINTED UNITS 	LABEL WITH PRINTED UNITS 
<b>Notes</b>	Labeling with printed units "Vdc", "mA", "%", "mm", "RPM", "m/min", "BAR", "°C" and "°".	Labeling with printed units "Vdc", "Vac", "Adc", "Aac", "mVdc", "mVac", "mAdc", "mAac" and "°".	Labeling with printed units "°C", "°F" and "°".	Labeling with printed units "mHz", "Hz", "KHz", "mSec", "Sec", "min", "Units", "RPM" and "°".	Labeling with printed units "mm", "cm", "m", "l", "m3", "RPM", "m/min", "Units" and "°".	Labeling with printed units "hrs", "min", "sec", "cent", "days", "time" and "°".

## How to order

Model	Power	Option1	Option2	Option3	Others
K40 - A	H	---	---	---	---
- P	- H (85-265Vac/dc)	- R1 (1 relay)	- R1 (1 relay)	- R1 (1 relay)	- 65 (IP65)
- T	- L (11-60Vdc and 24/48Vac)	- AO (Analog output)	- AO (Analog output)	- AO (Analog output)	- NBT (without front keypad)
- A		- RTU (MODBUS RTU)	- RTU (MODBUS RTU)	- RTU (MODBUS RTU)	
- D		- S4 (RS-485)	- S4 (RS-485)	- S4 (RS-485)	- (empty)
- R		- S2 (RS-232)	- S2 (RS-232)	- S2 (RS-232)	
- F		- (empty)	- (empty)	- (empty)	
- C1		- R2*			
- CR		- R4*			
- RTU		- R6*			
- 485					
- 232					

Note: Maximum 3 "Output and control options" on the instrument. Accepts all combinations and/or repetition of "Output and control options", unless otherwise indicated.

### \* Special options

- Module R2 2 relays Installed at Option 1
- Module R4 4 relays Installed at Option 1 and 2
- Module R6 6 relays Installed at Option 1, 2 and 3

For relay outputs, use options 'R1' as standard for 1, 2 and 3 relay outputs. Use "Special options" R2, R4 or R6 when modules R1 can not fill the requested application. Example: instrument with 3 relays and 1 Analog output, use 1xR4 and 1xAO (K40-P-H-R4-AO).

